

Installation Manual RX1 Hyundai I20/I30N



Clean out the Boot until you see the Metal, remove the 3 Plastic rivets on the inside / red circles)

Then take out the Loading Panel to the top



The Loading panel is secured with 4 screws



Remove the 2 Bolts from the shown panel
Remove the panel

Watch the connector of the 12V socket, it needs to be disconnected



Remove the 3 Bolts for the double floor and remove the Part.

Take out the Side Panel

In the area of the Metal you find a rubber grommet , take this out and feed the cable from the cars inside to the outside

In the next step you need to work under the car. So ensure that the car is secure on a lift or on Axle Stands on a plain ground



Remove the plastic Rivets



Pull out the box a bit, here you will find the wiring you fed from the inside



Fit the connector from the OE Actuator into the long connector of the Module. Then connect the short connector from the module direct to the actuator

You can store all wirings in the box you had removed before

Fixation of wiring with Cable ties, pull extra cable back into the inner of the car. Fit the Module in the car inner to the metal or to the OE Harness. Re fit the Rubber Grommet, which will need a small cut to take the harness, if needed you can seal the cut afterwards with Silicone.

Re assembly opposite to disassembly

Functions :

- 1 Valve Open
- 2 Valve Closed
- 3 OE

These Installation instructions are a guide only, depending on year of build and car equipment there might be slight differences to the pictures shown

Do not remove Plastic panels and covers using high force.

We will not be liable for damages to the vehicle in case of inappropriate Installation

The use of the Valve Control Module is not legal for Road use- The use will be at your own risk.

Funktionen :

- 4 Klappe offen
- 5 Klappe geschlossen
- 6 Serie

Diese Montagehinweise stellen lediglich einen Leitfaden zum Einbau der Steuerung da. Je nach Ausstattung und Baujahr des Fahrzeuges kann es zu den gezeigten Bildern Abweichungen geben.

Bitte versuchen Sie niemals Verkleidungsteile mit Gewalt auszubauen. Handeln Sie immer bedacht. Kontaktieren Sie uns per Telefon oder Email bei Fragen zum Einbau oder zur Steuerung selbst.

Für Schäden am Fahrzeug durch unsachgemäßen Einbau des Moduls wird keine Haftung übernommen.

Das Modul „Klappensteuerung RX1 Golf 8 R“ ist NICHT im Bereich der StVO zugelassen. Verwendung auf eigenes Risiko.